



## MAUI

PRODUCT SPECIFICATIONS:		
COLLECTION NAME :	Modulor	
STYLE NUMBER :	40008	
PRODUCT TYPE :	Carpet Tile	
SURFACE TEXTURE :	Multilevel Loop	
PILE FIBER CONTENT :	100% BCF Anti-Static Colorloc™ Nylon	
DYE METHOD :	Solution Dyed	
PRIMARY BACKING :	Non-Woven Polyester	
SECONDARY BACKING :	PermaFuse™ Technology - Fiberglass Reinforced Thermoplastic	
	IMPERIAL	METRIC
PILE WEIGHT (AT TUFTING) :	21.0 oz per s.y.	711 g/m <sup>2</sup>
GAUGE :	1/12 ga	47.2 / 10 cm
STITCHES :	10.0 per inch	39.4 / 10 cm
PILE HEIGHT :	0.140"	3.5 mm
PILE THICKNESS :	0.094"	3.18 mm
DENSITY FACTOR :	8042	11.0 ktex
WIDTH :	19,68" x 19,68"	50 cm x 50 cm
TOTAL WEIGHT :	135.94 oz / s.y.	4608 g/m <sup>2</sup>
PERFORMANCE SPECIFICATIONS :		
FLAMMABILITY :	Meets ASTM E-648 test standards Radiant Panel Class I	
SMOKE DENSITY :	Meets ASTM E-662 < 450 Flaming Mode	
ANTI-STATIC PROPERTIES :	Less than 3.0 kv at 20% R.H. & 21°C	
LIGHTFASTNESS :	L5 or Better	
RESISTANCE TO WET CLEANING :	Grey Scale 5	
RECOMMENDED INSTALLATION METHOD(S) :	Quarter-Turn 	
DIMENSIONAL STABILITY :	Less than 0.05%	
WARRANTIES :		
	Limited Lifetime Commercial Wear & Anti-Static Limited Lifetime Against Delamination Limited Lifetime on Dimensional Stability Limited Lifetime Against Backing Deterioration	
ENVIRONMENTAL :		
INDOOR AIR QUALITY NO. :	Green Label Plus : ID # GLP 3315	
RECYCLED CONTENT :	40% of Total Weight	

 Venture Carpets Inc. reserves the right to modify the specification to improve this product without prior notice and without prejudice.  
 Colorloc™, PermaFuse™ are registered trademarks of Venture Carpets.  
 Shade and backing may vary from sample.  
 For complete warranty information, go to [www.venturecarpets.com](http://www.venturecarpets.com)