

Venture

Modular

Product Specifications

Style Name	Celeste
Style Number	40261
Surface Texture	Multilevel Loop
Pile Fibre Content	100% Aquafil BCF ECONYL nylon
Dye System	Solution Dyed
Primary Backing	Non-Woven Polyester
Secondary Backing	Fiberglass Reinforced Thermoplastic - PermaFuse Technology - Phthalate Free

	<u>Imperial</u>	<u>Metric</u>
Pile Weight	21.0 oz / s.y.	712 g/m2
Gauge	1/12 ga	47.2 / 10 cm
Stitches	12.0 / in.	47.2 / 10 cm
Pile Height	0.195 in.	4.96 mm
Pile Thickness	0.118 in.	3.00 mm
Density Factor	6386	9.18 ktex
Total Weight	112.04 oz / s.y.	3798 g/m2


Performance Specifications

Flammability	Meets ASTM E-648 test standards Radiant Panel Class I
Smoke Density	Meets ASTM E-662 test standards <450 Flaming mode
Anti-Static Properties	Less than 3.0 kv at 20% R.H.. & 21° C
Dimensional Stability	Less than 0.05 %
Lightfastness	L5 or Better
Resistance to Wet Cleaning	Grey Scale 5
Acoustique ASTM-E3133	70
Acoustique ASTM-E492	60


Installation Method



Quarter-Turn



Brick



Ashlar

Warranty Information

- Lifetime Limited Commercial Wear & Anti-Static
- Lifetime Limited Commercial Against Delamination
- Lifetime Limited Commercial on Dimensional Stability
- Lifetime Limited Against Backing Deterioration

Environmental

Indoor air quality no.	GLP 3315
------------------------	----------

Dimension

Carpet Tile (PermaFuse)	19.68" x 19.68"	50 cm x 50 cm
-------------------------	-----------------	---------------

Manufacturer reserves the right to modify the specification to improve this product without prior notice and without prejudice