

Venture

Modular

Product Specifications

| | |
|--------------------|---|
| Style Name | Sirius |
| Style Number | 40262 |
| Surface Texture | Multilevel Loop |
| Pile Fibre Content | 100% Aquafil BCF ECONYL nylon |
| Dye System | Solution Dyed |
| Primary Backing | Non-Woven Polyester |
| Secondary Backing | Fiberglass Reinforced Thermoplastic - PermaFuse Technology - Phthalate Free |


| | Imperial | Metric |
|----------------|------------------|---------------|
| Pile Weight | 21.0 oz / s.y. | 712 g/m2 |
| Gauge | 1/12 ga | 47.2 / 10 cm |
| Stitches | 12.0 / in. | 47.2 / 10 cm |
| Pile Height | 0.195 in. | 4.96 mm |
| Pile Thickness | 0.118 in. | 3.00 mm |
| Density Factor | 6386 | 9.18 ktex |
| Total Weight | 112.04 oz / s.y. | 3798 g/m2 |

Performance Specifications


| | |
|----------------------------|---|
| Flammability | Meets ASTM E-648 test standards Radiant Panel Class I |
| Smoke Density | Meets ASTM E-662 test standards <450 Flaming mode |
| Anti-Static Properties | Less than 3.0 kv at 20% R.H.. & 21° C |
| Dimensional Stability | Less than 0.05 % |
| Lightfastness | L5 or Better |
| Resistance to Wet Cleaning | Grey Scale 5 |
| Acoustique ASTM-E3133 | 70 |
| Acoustique ASTM-E492 | 60 |
| Installation Method | |



Quarter-Turn



Brick



Ashlar

Warranty Information

- Lifetime Limited Commercial Wear & Anti-Static
- Lifetime Limited Commercial Against Delamination
- Lifetime Limited Commercial on Dimensional Stability
- Lifetime Limited Against Backing Deterioration

Environmental

| | |
|------------------------|----------|
| Indoor air quality no. | GLP 3315 |
|------------------------|----------|

Dimension

| | | |
|-------------------------|-----------------|---------------|
| Carpet Tile (PermaFuse) | 19.68" x 19.68" | 50 cm x 50 cm |
|-------------------------|-----------------|---------------|

Manufacturer reserves the right to modify the specification to improve this product without prior notice and without prejudice